

MASONRY SAW TBE350★★

CUTTING DEPTHS UP TO 110 MM



Swivelling saw head allows 45° mitre cuts to be made



Two robust castors provide optimum manoeuvrability at the deployment location



Included angle stop for cuts from 30° to 90°

- Uncompromising price/performance ratio
- Clean cutting thanks to solid saw table with non-slip surface
- Mitre cuts are child's play to make using the swivelling saw head
- Continuous tool cooling and minimal amount of service work due to water pump location that prevents soiling
- Problem-free transport thanks to removable table feet
- Maximum safety due to centrally located emergency stop switch
- High flexibility due to many adjusting and usage options

Technical data

| SAW BLADE | |
|--------------------|-----------|
| Max. cutting depth | 110 mm |
| Max. saw blade Ø | 350 mm |
| Cutting length | 600 mm |
| Saw blade speed | 2,800 rpm |
| Saw blade holder Ø | 25.4 mm |

| DRIVE | |
|----------------------------|---------------|
| Drive/motor | Electric |
| Output | 2.2 kW |
| Standard voltage/frequency | 230 V / 50 Hz |
| Optional voltage/frequency | 110 V / 60 Hz |
| Engine cooling | Air cooling |
| Saw blade drive | Direct |

| DESIGN | |
|--|--|
| Infinitely adjustable cutting depths | |
| Angle cutting function (angle stop) | |
| Mitre cutting function (swivelling saw head) | |
| Cap cutting function | |
| Water tank made from powder-coated steel | |
| Electric water pump | |
| Dismantlable | |

| DIMENSIONS & WEIGHT | |
|---------------------|----------|
| Length | 1,140 mm |
| Width | 640 mm |
| Height | 1,230 mm |
| Weight | 79 kg |

System

| MASONRY SAW TBE350** | | |
|----------------------|-----------------------------|--|
| 10981423 | Masonry saw TBE350S / 230 V | |
| 10981424 | Masonry saw TBE350S / 110 V | |